




Kit of L-Profile 5 Degree Tilt Legs

Component

						
R2-TL-5/L/C5 16 Units	R2-EC/28/36 4 Units	R2-IC/28/36 14 Units	R2-SP-BT 2 Units	R2-GC 8 Pcs	R2-GL-M 2 Units	R2-CC/2 16 PCs
R2 Kit of L-Profile 5 Degree Tilt Legs for 8 Panels, Version 2 Part No.: K-R2/TL-5/8/V2 (bar code: 21-290-00003)						

						
R2-TL-5/L/C5/BA 16 Units	R2-EC/28/36/BA 4 Units	R2-IC/28/36/BA 14 Units	R2-SP-BT 2 Units	R2-GC 8 Pcs	R2-GL-M 2 Units	R2-CC/2 16 PCs
R2 Kit of L-Profile 5 Degree Tilt Legs for 8 Panels, Version 2, Black Anodized Part No.: K-R2/TL-5/8/V2/BA (bar code: 21-290-00004)						

Technical Specification

Application	Tin Roof
Purlin requirement	Metal or Timber purlin
Screw specification	Buildex 14-11 x 70 (14 gauge, 6.3mm, 11TPI, 70mm long) Hex Head Zips Screw Climaseal 5
PV panel dimensions	For framed PV Modules of 28-36mm in height
Weight	K-R2/TL-5/8/V2: 6.680 Kg K-R2/TL-5/8/V2/BA: 7.608 Kg
Packaging	All components are packed together in 1 pack, 2 packs per carton
Material	Tilt Legs, Clamps, Splices, Rails: AL6005-T5 Grounding Clips, Cable Clips: SUS304 Grounding Lugs: AL6005-T5&SUS304
Standard	AS NZS1170.2-2021